

AGIP 7008



AGIP 7008 is a top quality lubricant specifically formulated to lubricate gasoline or diesel engines of cars of the Volkswagen Group, for which a “LongLife” lubricant meeting the VW 504 00 or 507 00 specifications is prescribed.

The product is also suitable to lubricate gasoline or diesel engines of the Volkswagen Group, for which oils meeting the a/m specifications have been admitted as an alternative to others originally specified.

CHARACTERISTICS (TYPICAL FIGURES)

AGIP 7008

SAE Grade		5W-30
Viscosity at 100 °C	mm ² /s	11,8
Viscosity at 40 °C	mm ² /s	72
Viscosity at -30 °C	mPa·s	6000
Viscosity Index	-	160
Flash Point COC	°C	235
Pour Point	°C	-45
Density at 15 °C	kg/l	0,850

PROPERTIES AND PERFORMANCE

- The product allows to reach the maximum oil drain intervals set by the engine manufacturer.
- AGIP 7008 is free-flowing at cold temperatures which allows easier engine startup.
- It is particularly suitable for those vehicles equipped with DPF (Diesel Particulate Filter), for which a longer operating life is allowed.
- It has high fuel economy characteristics, which turn into reduced fuel consumption and therefore reduced exhaust emissions.

SPECIFICATIONS

- Agip 7008 is by name officially approved by the Volkswagen Group against the VW 504 00 and 507 00 specifications.
- This product can be utilized in all engines that require lubricant which meet the VW 503.01 performance level.