

AGIP F.1 SUPERMOTOROIL



AGIP F.1 SUPERMOTOROIL is a general-purpose oil for every type of engine where the manufacturer recommends a multigrade oil or when the operator prefers to use only one grade throughout the year. It is suitable for spark-ignition and car diesel engines even when operating under the severest conditions involving, for instance, high-temperature motorway driving or low-temperature stop-go or taxi-service driving in towns.

CHARACTERISTICS (TYPICAL FIGURES)

AGIP F.1 SUPERMOTOROIL

SAE Grade		15W-40
Viscosity at 100°C	mm ² /s	14,5
Viscosity at 40°C	mm ² /s	109
Viscosity at -20°C	mPa.s	6800
Viscosity Index	-	130
Flash Point COC	°C	210
Pour Point	°C	-24
Mass density at 15°C	kg/l	0,884

PROPERTIES AND PERFORMANCE

- AGIP F.1 SUPERMOTOROIL has an extremely high Viscosity Index which keeps it free-flowing when cold and maintains high viscosity when hot. The same grade of lubricant can therefore be used in all seasons.
- Its superior detergent-dispersant properties effectively minimize the formation of lacquer and varnish, as well as other deposits, definitively avoiding the formation of the so called "black sludge".
- AGIP F.1 SUPERMOTOROIL thus helps prevent ring sticking, keeps pistons clean and maintains deposits in suspension.
- AGIP F.1 SUPERMOTOROIL is highly resistant to deterioration especially that caused by oxidation due to prolonged high-temperature operation in the presence of air and other agents.
- It has special anticorrosion properties which afford effective protection against corrosion by combustion moisture and acids.
- Its antiwear properties ensure long life for all moving parts, substantially reducing the need for engine servicing and overhauls.
- Its antifoam properties prevent the formation of air bubbles which could affect lubricant film continuity.
- Its special formulation ensures superior performance without the need for a high percentage of organo-metallic additives. This reduces combustion chamber deposits, thus lessening the danger of preignition, while effectively containing the rise in the octane requirement after prolonged engine operation.

AGIP F.1 SUPERMOTOROIL



SPECIFICATIONS

AGIP F.1 SUPERMOTOROIL is officially approved or meets the requirements of the following services and specifications:

- API Service SL/CF
- ACEA A3, B3
- MB 229.1
- US Department of the Army MIL-L-46152D
- CCMC G4, PD2
- Ford SSM - 2C 9011 - A
- Ford USA - ESE - M2C 153 - C
- General Motors 6085 M
- Rover RES.22.OL.02.G-4
- Volkswagen 501.01 + 505.00 (11/92)