

AGIP CITY 2T



AGIP CITY 2T is a lubricant with very low exhaust smoke levels for the latest generation of two-stroke engines of scooters. It is formulated with special synthetic components which make it particularly suitable for use in both air- and water-cooled engines.

AGIP CITY 2T, though formulated specifically for oil injection systems, can be used for premix mixtures as well. The product can also be employed in mixtures with unleaded gasoline.

CHARACTERISTICS (TYPICAL FIGURES)

AGIP CITY 2T

Viscosity at 100°C	mm ² /s	11,8
Viscosity at 40°C	mm ² /s	94
Viscosity Index	-	115
Flash Point COC	°C	125
Pour Point	°C	-24
Mass Density at 15°C	kg/m ³	0,874

PROPERTIES AND PERFORMANCE

- AGIP CITY 2T minimizes deposit formation in the combustion chamber, the ring area and the exhaust system, while reducing spark-plug fouling and ensuring that the components remain clean.
- Careful selection of the synthetic base results in very low exhaust smoke levels.
- The product has superior "self-mixing" properties thus guaranteeing very rapid mixing with the gasoline, for use on engines fitted with oil injection systems.
- AGIP CITY 2T provides excellent protection against engine corrosion, rust and wear.

SPECIFICATIONS

AGIP CITY 2T meets the requirements of the following specifications:

- API TC
- JASO FC